

thindunt
sed dier
amet, a
nulle fac
dient a
dient a
accuse
reperit n
modeste
hendit
Duis aut
adipic e
ultram
vernam,
voluptat
laoreet,
natum
consect
Lorem
eiusm
Lorem
Lol



100 | 100



Address Book

01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

On Hook Dial

Pause/Retial

Shift

Duplex 100% Mixed A4 01

Menu

OK

1 2 ABC 3 DEF 4 GHI 5 JKL 6 MNO 7 PQRS 8 TUV 9 WXYZ * 0 @ - #

LANIER

Compact all-round functionality

It's all about user friendly operation and efficiency with the flexibility that only a multifunctional device provides.

SP3410SF



LANIER

Making your documents our business

SP3410SF

SPECIFICATIONS AND INFORMATION

Compact all-round functionality

COPIER

Technology:	Reading element: Flatbed with CCD array image-sensor
Printing processing:	Laser beam scanning & Electro photographic printing Mono component toner development
Print Speed:	28 prints per minute (A4)
Resolution (H x V):	600 x 600dpi (Maximum)
Multiple Print:	Up to 99
Warm-up Time:	Less than 30 seconds
First copy speed:	Platen/ADF Platen: 12 seconds / ADF: 11 seconds
Zoom	25-400% (in 1% steps)
RAM:	Standard: 128MB
Input capacity:	Standard Tray: 250 sheets (80 g/m ²)
Bypass tray:	50 sheets (80 g/m ²)
Optional Paper Tray:	Paper Feed Unit: 250 sheets (80 g/m ²)
Maximum:	up to 550 sheets
ADF:	Capacity: 35 sheets (80g/ m ²)
Input Paper Size:	Standard Tray: A4 - A6
Bypass Tray:	A4 - A6
Optional Paper Tray:	A4 - A5
Paper Weight:	Standard Tray: 52-162g/m ²
Bypass tray:	52-162g/m ²
Op. Paper Tray:	60-105g/m ²
Duplex:	60-105g/m ²
Dimensions:	420 x 397 x 442 mm
Weight:	Less than 18kg
Rating Power Spec.:	220-240V, 50/60Hz
Power Consumption:	Maximum: 895W
Energy Saver:	10W
Quick mode (10 sec):	70W

PRINTER

Printing Speed:	28 ppm (A4)
Resolution	600 x 600 dpi
Interface:	USB2.0, 100 Base-TX/ 10 Base-T Ethernet
Duplex:	Automatic
Operating Systems:	Windows 2000/ XP/ Server2003/ Vista/ Server 2008 Mac OS X (v 10.2.8 - 10.5)

SCANNER

Scan modes/ speed (A4, 300dpi, USB2.0):	ADF B/W: less than 5 sec. Gray Scale: less than 5 sec. Color: less than 10 sec. Platen B/W: less than 5 sec. Gray Scale: less than 5 sec. Color: less than 10 sec.
Resolution: Scanner:	1200 x1200 dpi
Driver:	Maximum 19200 x 19200 dpi (interpolated)
Maximum original size:	Platen: Width: Up to 216mm
Length:	Up to 297mm
ADF:	Width: Up to 216mm
Length:	Up to 356mm
Scanner utilities & Drivers:	TWAIN Driver, Scanner utility (PageManager)

FAX

Circuit:	PSTN/PBX
Compatibility:	ITU-T G3
Modem Speed:	33.6kbps (Maximum)
Coding System	
Compression Method:	MH/ MR/ MMR
Speed Dial:	50 locations
One Touch Dial:	20 locations
SAF Memory:	100 pages (ITU No.1 chart, Compression: MMR, Resolution: Standard)

CONSUMABLES

Toner (Starter):	Approx. 1500 prints/ctrig *
Toner:	Approx. 5000 prints/ctrig *

ADDITIONAL OPTIONS

Accessories:	Paper Feed Unit
--------------	-----------------

***Condition:**

- 1) ISO/IEC19752 is used to measure the above toner yield.
- 2) The condition is standard temperature and humidity.
- 3) This yield number may change depending on the circumstances and printing conditions.

For more information please contact:

Lanier (Australia) Pty Ltd HEAD OFFICE
854 Lorimer Street | Port Melbourne | Victoria 3207

SYDNEY Branch Office
3 Chaplin Drive | Lane Cove | NSW 2066

BRISBANE Branch Office
Unit 3/ 57Miller Street | MURARRIE | QLD 4172

PERTH Branch Office
19 Collingwood Street | Osborne Park | WA 6017

Lanier Customer Care: 1300 362 345
www.lanierprinters.com.au



LANIER

Making your documents our business